



Micronica MIC-1900T 19" LCD Touch Screen Monitor

Features:

- High brightness & high contrast TFT panel.
- Universal power supply.
- Wide view angel support.
- Low power consumption.
- Low power saving mode.
- Resistive or SAW touch screen choice.
- USB, D-Sub, DVI, Audio & DC connector.
- Green monitor.
- Swing stand design.
- With accurate handwriting function.
- Substitution of the traditional mouse and keyboard.

Specification:

- LCD Panel: 19.0" TFT, LVDS
- Response Time: 5 ms.
- Viewing Angle: -85~85 °(H), -85~85 °(V).
- View Area: 376.3 x 301.1 mm.
- Resolution: 1280x 1024 SXGA.
- Display Colors: 16.7 M (8 bits/color).
- Pixel Pitch: 0.294 (H) x 0.294 (V) (mm).
- Contrast Ratio: 2000:1 high contrast.
- Brightness: 300 cd/m2.
- Audio: 2w x 2.
- Temperature : -5°C~50°C operating, -20°C~70°C storage.
- Connector type: D-sub/DC/Audio/DVI/USB.
- Optional connector : HDMI/AV/S-video/RS-232/BNC.
- Power Supply: AC 90~240V, 50~60Hz.
- Power management: VESA-DPMS (Max.) : < 30W. Saving mode < 1W.
- User's Control: power on/off, OSD control.
- Dimension (mm): 440 x 470 x 220 mm.
- Carton dimension : 500(L) x 520(W) x 270(D) mm.
- Weight: 7.5 Kgs/Net, 9.0Kgs/gross.
- Safety certifications: FCC, CE, RoHS, EnergyStar.
- Environmental Condition: Operation temperature): 0~50°C .
- Storage temperature: -20~70°C .
- Humidity/Moisture: 10%~90%.
- Specifications are subject to change without notice.

* Accessories: 100~240V /48W universal power adaptor, power cord, audio cable, USB cable, Driver CD & user manual. Or built in power supply. Please specify when ordering.



184 Napier St, South Melbourne, 3205, Victoria, AUSTRALIA

T:03-96998844 F:03-96905331 E:sales@micronica.com.au

www.micronica.com.au